



www.xlam.biz

# Xlam

## XL1600 cold 2.0



main rolls Ø

130 mm

max. temperature

60 °C

max. material thickness

30 mm

Functional design ✓



Pneumatic lifting ↑



Optional Blades Kit for trimming 🍷





# XL1600 cold 2.0

## PNEUMATIC COLD LAMINATOR

[www.xlam.biz](http://www.xlam.biz) / [info@xlam.biz](mailto:info@xlam.biz)

### Unique features!

Cold roll-to-roll pneumatic laminator 1600 mm. Take-Up system included. **Silicone roll (heated) 130mm**, maximum temperature 60°C. **Material thickness up to 30mm**.

Quick and easy to use, it allows you to save labor and improve productivity by increasing the quality of your work. Moreover, from today you can also laminate without liner with **"linerless" laminations**.

### High efficiency

No crease or bubble, it guarantees excellent results even at temperatures below 60°C. **Equipped with footswitch feeding**, it allows the operator to keep both hands free for the rolling of wider supports.

### Safety warranty

The **photocell sensor** prevents you place your hands near roll during the lamination. The emergency shutdown button is clearly visible on the front of the machine.

**Product code**  
XL1600C2.0

**Main silicon rolls diameter**  
130 mm

**Packaging**  
anti-shock wooden

**Maximum laminating film width**  
1600 mm

**Main roll moving**  
by air compressor

**Dimensions (l x h x p)**  
1980 x 1350 x 630 mm

**Maximum material thickness**  
30 mm

**Footswitch feeding**  
included

**Packaging dimensions (l x h x p)**  
2250 X 720 x 810 mm

**Maximum temperature**  
60 °C

**Take-Up system**  
included

**Machine / packaging weight**  
175 kg / 190 kg

**Minimum-maximum speed**  
2,30 - 11,55 lmt/min

**Heating method**  
internal with resistance

**Safety**  
photocell / CE certification

**Temperature-speed control**  
Micro Control

**Maximum power / Voltage**  
2500 W / 220 v - 50 hz

**Warranty**  
12 months



Authorized Reseller

 **Print**  
**GROSSISTEN**